

CASE
CONSTRUCTION

400 SERIES 3 SKID STEER LOADERS

410 | 420 | 430 | 435 | 440 | 445 | 450 | 465



Case Delivers Full-Service Solutions

EQUIPMENT | FINANCING | PARTS & SERVICE

400 SERIES 3 SKID STEER LOADERS

	410	420	430	435
Engine	57 net hp (42 kW)	69 net hp (52 kW)	77 net hp (57 kW)	77 net hp (57 kW)
Operating load	1,500 lb (681 kg)	1,850 lb (839 kg)	2,000 lb (907 kg)	2,200 lb (998 kg)
Bucket breakout force	4,654 lbf (20 702 N)	5,500 lbf (24 464 N)	5,784 lbf (25 728 N)	6,681 lbf (28 024 N)
Bucket hinge pin height	114.9 in (2.92 m)	120.7 in (3.06 m)	121.6 in (3.09 m)	120.0 in (3.05 m)
Operating weight	5,430 lb (2463 kg)	6,605 lb (2996 kg)	6,800 lb (3084 kg)	6,780 lb (3075 kg)
Biodiesel compatibility	B5	B5 or B20*	B5 or B20*	B5 or B20*

	440	445	450	465
Engine	83 net hp (62 kW)	77 net hp (57 kW)	83 net hp (62 kW)	83 net hp (62 kW)
Operating load	2,200 lb (998 kg)	2,500 lb (1134 kg)	2,450 lb (1111 kg)	3,000 lb (1361 kg)
Bucket breakout force	6,207 lbf (27 610 N)	7,400 lbf (32 917 N)	7,213 lbf (32 085 N)	7,400 lbf (32 917 N)
Bucket hinge pin height	121.5 in (3.09 m)	122.4 in (3.11 m)	124.5 in (3.16 m)	125.5 in (3.19 m)
Operating weight	7,040 lb (3193 kg)	8,120 lb (3683 kg)	8,630 lb (3915 kg)	8,875 lb (4026 kg)
Biodiesel compatibility	B5	B5 or B20*	B5 or B20*	B5 or B20*

* B20 approved following Case guidelines for biodiesel blends above five percent.



410



420



430



435



440



445



450



465

NOTE: All engines meet current EPA emission regulations.

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

IMPORTANT: Case Construction Equipment Inc. reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Availability of some models and equipment builds vary according to the country in which the equipment is used. The illustrations and text may include optional equipment and accessories and may not include all standard equipment. Your Case dealer/distributor will be able to give you details of the products and their specifications available in your area.



Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs and use any safety features provided.

©2008 CNH America LLC. All rights reserved. Case is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. Printed in U.S.A.

Form No. CCE4140803



Case construction equipment is biodiesel ready.



Looking for product specs, customer testimonials, competitive comparisons, finance offers and more?
Visit us at www.casece.com or call 866-54CASE6