

CASE
CONSTRUCTION

M SERIES 3 LOADER/BACKHOES

580 M | 580 Super M | 580 Super M+ | 590 Super M | 590 Super M+



Case Delivers Full-Service Solutions

EQUIPMENT | FINANCING | PARTS & SERVICE

M SERIES 3 LOADER / BACKHOES

580	M	Super M	Super M+
Engine	79 net hp (59 kW)	91 net hp (68 kW)	95 net hp (71 kW)
Backhoe dig depth	14 ft 3 in (4.34 m)	14 ft 5 in (4.39 m)	14 ft 10 in (4.65 m)
Backhoe bucket force	11,212 lbf (49 873 N)	12,821 lbf (57 031 N)	12,821 lbf (57 031 N)
Loader	6,182 lb (2804 kg)	6,182 lb (2804 kg)	6,182 lb (2804 kg)
Operating at full weight	16,510 lb (7489 kg)	17,545 lb (7958 kg)	18,128 lb (8223 kg)
Biodiesel compatibility	B5 or B20*	B5 or B20**	B5 or B20**



580 M

590	Super M	Super M+
Engine	108 net hp (81 kW)	108 net hp (81 kW)
Backhoe dig depth	15 ft 11 in (4.85 m)	15 ft 11 in (4.85 m)
Backhoe bucket force	14,718 lbf (65 469 N)	14,718 lbf (65 469 N)
Loader	7,327 lb (3323 kg)	7,327 lb (3323 kg)
Operating at full weight	19,578 lb (8881 kg)	19,578 lb (8881 kg)
Biodiesel compatibility	B5 or B20**	B5 or B20**



580 Super M



580 Super M+

* B20 approved following Case guidelines for biodiesel blends above five percent.

** B20 approved following Case HPCR engine guidelines for biodiesel blends above five percent.

NOTE: All engines meet current EPA emission regulations.

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

IMPORTANT: Case Construction Equipment Inc. reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Availability of some models and equipment builds vary according to the country in which the equipment is used. The illustrations and text may include optional equipment and accessories and may not include all standard equipment. Your Case dealer/distributor will be able to give you details of the products and their specifications available in your area.



Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs and use any safety features provided.

©2008 CNH America LLC. All rights reserved. Case is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. Printed in U.S.A.

Form No. CCE12040701R Replaces Form No. CCE12040701



Contains 10% Post-Consumer Fiber



Case construction equipment is biodiesel friendly.



590 Super M



590 Super M+



Looking for product specs, customer testimonials, competitive comparisons, finance offers and more?
Visit us at www.casece.com or call 866-54CASE6