

Platform

0.66 m x 0.66 m (W x L) Slide bar side entry platform

Quick-change platform mounts

Safety interlocked controls

Load sensing system

Lanyard attach points

AC power cable to platform

Power & Transmission

6 wheel chassis with 'X' pattern outriggers

Outrigger interlocks with LED indicators

Non mark tyres and casters

Roller loading device

¹ Includes 5 hour battery charger

² Applicable to battery powered DC models only

Functional Equipment & Accessories

Low maintenance anodised aluminium mast

Spring loaded sequence cables

Manual descent

Key lock main power switch

Hour meter

Transportation tie-down lugs

Fork truck pockets

Available Options

0.56 m x 0.64 m (W x L) Narrow slide bar entry platform

110V or 230V mains power operation (AC models)

12V 100 A/hr deep cycle battery operation (DC models)

Sealed 12V 100A/hr maintenance free AGM battery ¹

Detachable battery & charger compartment ²

20 amp automatic battery charger ²

Straddle extension kit with 1.09 m clearance

Straddle extension kit with 1.40 m clearance

Battery condition indicator ²

Programmable 4 digit security lock

Lifting eye for crane hook

Fluorescent tube caddy

Tool tray (0.20 m x 0.46 m x 0.13 m)

Descent alarm

Emergency lowering control

Amber strobe light

JLG Industries Inc.

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 2493
e-mail address: europe@jlg.com
www.jlgeurope.com
An Oshkosh Corporation Company

Printed in UK
FORM No.: DS028-0208-500
PART NO.: DS028-ENGLISH



30AM

Platform height	9.14 m
Working height	11.14 m
Platform capacity	135 kg
Platform size - narrow (W x L)	0.56 m x 0.63 m
Platform size - side entry (W x L)	0.66 m x 0.66 m
Platform size - extension (W x L)	—
Overall height - stowed	1.97 m
Overall height - tilted back	—
Base width - stowed	0.74 m
Base length - stowed	1.32 m
Base length - without platform	1.19 m
Overall length - tilted back	—
Ground entry height	0.48 m
Outrigger footprint length	1.88 m
Outrigger footprint width	1.83 m
Distance to wall - front	0.20 m
Distance to wall - side	0.60 m
Machine weight - AC *	395 kg
Machine weight - DC *	430 kg
Rear wheel diameter	25 cm
Caster wheel diameter	15 cm

*Certain options or country standards may increase weight and/or dimensions.