

## Articulating Boom Lifts

## JLG Model 600AJ Narrow

### Platform

0.91 m x 1.83 m low mount platform

Side entry with inward swing gate

Multiple function operation

Full proportional drive joystick control with integral thumb steer switch

Full proportional main boom and swing joystick control

Variable speed dial control for lower boom, telescope and platform rotate

Selectable creep speed on drive / lift and swing functions

1.83 m articulating jib

180 degree powered platform rotator

Platform console machine status light panel <sup>1</sup>

Load sensing system

AC power cable to platform

### Power & Transmission

Deutz D2011L04 (37 kW) diesel engine

Engine distress warning /shut down system <sup>2</sup>

Gull-wing turntable hoods

Swing-out engine tray

Spark arresting type muffler

Control ADE™ (Advanced Design Electronics) System

Hydrostatic drive transmission

Horn

**JLG Industries Inc.**  
 Polaris Avenue 63  
 2132 JH Hoofddorp  
 The Netherlands  
 Tel: +31 (0)23 565 5665  
 Fax: +31 (0)23 557 2493  
 e-mail address: europe@jlg.com  
**www.jlgeurope.com**  
 An Oshkosh Corporation Company

Printed in UK  
 FORM No.: DS043-0208-500  
 PART NO.: DS043-ENGLISH

### Functional Equipment & Accessories

3 degree tilt alarm and indicator light

IN 355/55D 625 foam filled lug tread tyres

Lifting/tie down lugs

Hour meter

Ground control selector switch with key lock

Platform tool tray

12V-DC auxiliary power

### Available Options

0.91 m x 2.44 m low mount platform

13 mm air line to platform

Four wheel drive

Four wheel steer/Two wheel steer/Crab steer <sup>3</sup>

Oscillating front axle

On-board 2500W generator

SkyPower™ package 7,500 watt on-board generator

SkyWelder™ package 250 amp welder in the platform <sup>4</sup>

<sup>1</sup> Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.

<sup>2</sup> Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

<sup>3</sup> Only available with four wheel drive on models 600A and 600AJ with 2.4m wide chassis and 800A and 800AJ. Only available with two wheel drive on models n600A and n600AJ with 2.13m chassis.

<sup>4</sup> Available when integrated with the SkyPower™ package

<sup>5</sup> Consists of six 40-watt lights, four turntable mounted lights and two platform mounted lights.

<sup>6</sup> Includes all-motion alarm and flashing amber beacon.

<sup>7</sup> Includes platform mounted work lights and head & tail lights.

<sup>8</sup> Includes console cover, boom wipers and cylinder bellows.

### Available Options

Nite-Bright® package platform mounted lights <sup>5</sup>

Tow package

All motion alarm

Alarm package <sup>6</sup>

Light package <sup>7</sup>

Head and tail lights

Flashing amber beacon

Plugs & Sockets

Hostile environment package <sup>8</sup>

Catalytic purifier muffler

Soft Touch proximity system

Corner storage tray



**JLG**®

## Articulating Boom Lifts

## JLG Model 600AJ Narrow

## 600AJ Narrow

Platform height	18.46 m
Horizontal outreach	11.81 m
Up and over height	8.09 m
Swing (continuous)	360°
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	180°
Jib – overall length	1.83 m
Jib - range of articulation	130° (+70°/ -60°)
A. Platform size	0.91 m x 1.83 m
B. Overall width	2.45 m
C. Tailswing – working condition	Zero
D. Stowed height	2.56 m
E. Stowed length	8.82 m
F. Wheelbase	2.44 m
G. Ground clearance	0.30 m
Machine weight <sup>1</sup>	10,830 kg
Maximum ground bearing pressure	5.30 kg/cm <sup>2</sup>
Drive speed 2WD	6.8 km/h
Drive speed 4WD	6.8 km/h
Gradeability 2WD	30%
Gradeability 4WD	45%
Tyres	IN 355/55 D625 Foam Filled
Axle oscillation	0.20 m <sup>2</sup>
Turning radius – inside 2WS	3.30 m
Turning radius – inside 4WS	1.46 m
Turning radius – outside 2WS	5.56 m
Turning radius – outside 4WS	3.73 m
Diesel engine – Deutz D2011L04	37 kW
Diesel engine – (option) CAT 3.4	47 kW
Fuel tank capacity	114 L
Hydraulic reservoir	139 L
Auxiliary power	12V DC

<sup>1</sup> Certain options or country standards may increase weight and/or dimensions.

<sup>2</sup> Optional.

<sup>3</sup> With EGR.

