

SCANCLIMBER® SC8000

SC8000

New

our **strongest**
mast climbing work platform

The perfect solution for
bricklaying and other
heavy works



Modular system

- same mast sections and wheel chassis as in SC1300, SC4000 and SC5000 models
- same platforms as in SC5000



Technical data	SC8000 single	SC8000 twin
• Max. platform length / loading capacity	4,1 m / 4500 kg 7,3 m / 4100 kg 10,5 m / 3700 kg 13,7 m / 3250 kg 16,9 m / 2800 kg	15,8 m / 8000 kg 20,6 m / 7800 kg 25,4 m / 7200 kg 30,2 m / 5600 kg 35,0 m / 4600 kg 40,6 m / 3600 kg 46,2 m / 1000 kg
• Max. freestanding height		
- with full extended outriggers	15 m	15 m
- with one side extended outriggers	10 m	10 m
• Max. height with top anchor	25 m	25 m
• Max. height with mast anchored	150 m	150 m
• Distance between anchors	12,5 m	12,5 m
• Lifting speed	8,5 m / min	8,5 m / min
• Mast sections hot-dip galvanized	1,25 m / 82 kg	1,25 m / 82 kg
• Electric system:		
- lifting motors	3-phase/400 V/50 Hz	3-phase/400 V/50 Hz
- drive motor	circuit breaker C 32 A	63 A
• Safety devices:		
- mechanical safety brake	♦	♦
- emergency stop and limit switches	♦	♦
- electromagnetic brake	♦	♦
- phase sequence relay	♦	♦
- residual current device	♦	♦

OY SCANINTER NOKIA LTD

Turkkirata 26

FI-33960 PIRKKALA, FINLAND

Tel. +358 10 680 7000 Fax +358 10 680 7033

www.SCANCLIMBER.com