

MG 10 I-H/AE

THREE-PHASE POWER GENERATOR / OUTPUT POWER **10 KVA**
THREE-PHASE AND **4 KVA** SINGLE-PHASE /
PETROL ENGINE **3000 RPM**

Gen Set Features

- + Low oil level cut out device
- + 12V built-in battery with electric start
- + 1 x 16A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker
- + 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker
- + Earth Leakage Circuit Breaker (ELCB)
- + Voltmeter
- + Central lifting eye

Gen Set Options (available as factory options)

- + Versions with different voltages
- + 60 Hz version
- + AMF/ATS panel for auto start operation

Accessories on Request

- + Trolley: two-wheels and handles
- + Spark arrester muffler (Honda)

Noise Level

- + LWA 98 (73 dB at 7m)

AC Generator 50 Hz

- + Type synchronous
- + Three-phase power (stand by) 10 kVA – 400 V
- + Three-phase power (prime) 9 kVA – 400 V
- + Single-phase power (max.) 4 kVA - 230 V
- + Power Factor 0,8

Petrol Engine 3000 rpm

- + Type **Honda GX 620 K1** - 2 cyl. - 20 HP (14,8 kWm) - 614 cm³
- + Fuel petrol
- + Cooling system air
- + Starting system electric
- + Fuel tank capacity 29 l
- + Fuel consumption @ 75% 4,8 l/h

Other Features

- + Insulation Class H
- + Mechanical Protection IP 23
- + Dimensions (L x W x H) 850 x 477 x 760 mm
- + Dry Weight 148 kg

MG 10 I-H/AE

