

MG 10/8 S-K

SILENCED THREE-PHASE POWER GENERATOR / OUTPUT POWER
10 KVA THREE-PHASE AND **8 KVA** SINGLE-PHASE /
DIESEL ENGINE **3000 RPM**

Gen Set Features	<ul style="list-style-type: none">+ DAS, auto engine protection shutdown system with warning lights in case of:<ul style="list-style-type: none">- battery charger failure- high coolant temperature- low fuel level- low oil pressure+ 12V built-in battery with electric start+ Engine hourmeter+ Fuel level gauge+ 1 x 16A, 400 V - 50 Hz three-phase EEC socket+ 1 x 32A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ Earth Leakage Circuit Breaker (ELCB)+ Voltmeter+ Central lifting eye		
Gen Set Options (available as factory options)	<ul style="list-style-type: none">+ Spark arrester muffler+ Versions with different voltages+ 60 Hz version+ AMF/ATS panel for auto start operation+ Engine water heaters powered by mains 230 V - 50 Hz		
Accessories on Request	<ul style="list-style-type: none">+ Trolley: two-wheels and handles+ Two-wheels site tow undercarriage (GRT2W)		
Noise Level	+ Lwa 97	(72 dB at 7m)	Homologated in accordance with the "Directive 2000/14/EC"
AC Generator 50 Hz	<ul style="list-style-type: none">+ Type Gen Set asynchronous self-excited and self-protected+ Three-phase power (stand by) 10 kVA - 400 V+ Three-phase power (prime) 9 kVA - 400 V+ Single-phase power (max.) 8 kVA - 230 V+ Power Factor 0,8		
Diesel Engine 3000 rpm	<ul style="list-style-type: none">+ Type Kubota D722 - 3 cyl. - 17 HP (12,5 kWm) - 719 cm³+ Fuel diesel+ Cooling system water	<ul style="list-style-type: none">+ Starting system electric+ Fuel tank capacity 42 l+ Fuel consumption @ 75% 2,9 l/h	
Other Features	<ul style="list-style-type: none">+ Insulation Class F+ Mechanical Protection IP 23+ Dimensions (L x W x H) 1385 x 660 x 915 mm+ Dry Weight 385 kg		

MG 10/8 S-K

 **GenSet**

