

## MG 10/8 SS-K

SUPER SILENCED THREE-PHASE POWER GENERATOR / OUTPUT POWER **10 KVA** THREE-PHASE AND **8 KVA** SINGLE-PHASE / DIESEL ENGINE **3000 RPM**

<b>Gen Set Features</b>	<ul style="list-style-type: none"> <li>+ DAS, auto engine protection shutdown system with warning lights in case of:               <ul style="list-style-type: none"> <li>- battery charger failure</li> <li>- high coolant temperature</li> <li>- low fuel level</li> <li>- low oil pressure</li> </ul> </li> <li>+ 12V built-in battery with electric start</li> <li>+ Engine hourmeter</li> <li>+ Fuel level gauge</li> <li>+ 1 x 16A, 400 V - 50 Hz three-phase EEC socket</li> <li>+ 1 x 32A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker</li> <li>+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker</li> <li>+ Earth Leakage Circuit Breaker (ELCB)</li> <li>+ Voltmeter</li> <li>+ AMF connector / RC connector</li> <li>+ Emergency STOP button</li> <li>+ Manual oil sump pump</li> <li>+ Bunded base to retain all liquids</li> <li>+ Central lifting eye</li> </ul>		
<b>Gen Set Options</b> (available as factory options)	<ul style="list-style-type: none"> <li>+ Spark arrester muffler</li> <li>+ Versions with different voltages</li> </ul>	<ul style="list-style-type: none"> <li>+ 60 Hz version</li> <li>+ Engine water heaters powered by mains 230 V - 50 Hz</li> </ul>	
<b>Accessories on Request</b>	<ul style="list-style-type: none"> <li>+ Two-wheels site tow undercarriage (GRT2W)</li> <li>+ AMF/ATS panel for auto start operation</li> <li>+ Remote Start/Stop kit by cable (20m)</li> </ul>		
<b>Noise Level</b>	+ Lwa 93	(68 dB at 7m)	Homologated in accordance with the "Directive 2000/14/EC"
<b>AC Generator 50 Hz</b>	<ul style="list-style-type: none"> <li>+ Type Gen Set asynchronous self-excited and self-protected</li> <li>+ Three-phase power (stand by) 10 kVA - 400 V</li> <li>+ Three-phase power (prime) 9 kVA - 400 V</li> <li>+ Single-phase power (max.) 8 kVA - 230 V</li> <li>+ Power Factor 0,8</li> </ul>		
<b>Diesel Engine 3000 rpm</b>	<ul style="list-style-type: none"> <li>+ Type <b>Kubota D722</b> - 3 cyl. - 17 HP (12,5 kWm) - 719 cm<sup>3</sup></li> <li>+ Fuel diesel</li> <li>+ Cooling system water</li> </ul>	<ul style="list-style-type: none"> <li>+ Starting system electric</li> <li>+ Fuel tank capacity 74 l</li> <li>+ Fuel consumption @ 75% 2,9 l/h</li> </ul>	
<b>Other Features</b>	<ul style="list-style-type: none"> <li>+ Insulation Class F</li> <li>+ Mechanical Protection IP 23</li> <li>+ Dimensions (L x W x H) 1385 x 645 x 1050mm</li> <li>+ Dry Weight 385 kg</li> </ul>		

## MG 10/8 SS-K

