

MG 140 S-DZ

SILENCED THREE-PHASE POWER GENERATOR / OUTPUT POWER **137 KVA** THREE-PHASE AND **45,5 KVA** SINGLE-PHASE / DIESEL ENGINE **1500 RPM**

Gen Set Features	<ul style="list-style-type: none"> + Voltmeter + Ammeter + Engine hourmeter + DAS, auto engine protection shutdown system with warning lights in case of: <ul style="list-style-type: none"> - battery charger failure - high coolant temperature - low fuel level - low oil pressure - overspeed 	<ul style="list-style-type: none"> + Main circuit breaker + Fuel level gauge + Automatic Voltage Regulator (AVR) + Electronic frequency regulator + Three-phase output terminal board + Emergency STOP button + AMF connector / RC connector + Side lifting eyes 	
Gen Set Options (available as factory options)	<ul style="list-style-type: none"> + 60 Hz version + Versions with different voltages + Earth Leakage Circuit Breaker (ELCB) + Long run fuel tank (24h) complete with bunded base + Engine water heaters powered by mains 230 V - 50 Hz 	<ul style="list-style-type: none"> + Spark arrester muffler + Set mounted distribution board with three and single-phase outlets protected by circuit breakers and ELCB + Separate tank facility c/w quick release couplings 	
Accessories on Request	<ul style="list-style-type: none"> + Two-wheels site tow undercarriage (GRT2W) + Remote Start/Stop kit by cable (20m) + AMF/ATS panel for auto start operation 		
Noise Level	+ LWA 97	(72 dB at 7m)	Homologated in accordance with the "Directive 2000/14/EC"
AC Generator 50 Hz	<ul style="list-style-type: none"> + Type + Three-phase power (stand by) + Three-phase power (prime) + Single-phase power (max.) + Power Factor 	<ul style="list-style-type: none"> synchronous 137 kVA - 400 V 130 kVA - 400 V 45,5 kVA - 230 V 0,8 	
Diesel Engine 1500 rpm	<ul style="list-style-type: none"> + Type Deutz BF4M 1013 FC - turbocharged - 4 cyl. - 162,9 HP (119,7 kWm) - 4764 cm³ + Fuel + Cooling system + Starting system + Fuel tank capacity + Operating hours @ 75% 		
Other Features	<ul style="list-style-type: none"> + Insulation Class + Mechanical Protection + Dimensions (L x W x H) + Dry Weight 	<ul style="list-style-type: none"> H IP 23 3100 x 1100 x 1555 mm 1800 kg 	

MG 140 S-DZ

