

## MG 15/10 S-L

SILENCED THREE-PHASE POWER GENERATOR / OUTPUT POWER  
**15 KVA** THREE-PHASE AND **10 KVA** SINGLE-PHASE /  
DIESEL ENGINE **3000 RPM**

<b>Gen Set Features</b>	<ul style="list-style-type: none"><li>+ DAS, auto engine protection shutdown system with warning lights in case of:<ul style="list-style-type: none"><li>- battery charger failure</li><li>- low fuel level</li><li>- low oil pressure</li></ul></li><li>+ Automatic idle device when no load is connected</li><li>+ 12V built-in battery with electric start</li><li>+ Engine hourmeter</li><li>+ Fuel level gauge</li><li>+ 1 x 32A, 400 V - 50 Hz three-phase EEC socket</li><li>+ 1 x 32A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker</li><li>+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker</li><li>+ Earth Leakage Circuit Breaker (ELCB)</li><li>+ Voltmeter</li><li>+ Central lifting eye</li><li>+ Two-wheels site tow undercarriage (GRT2W)</li></ul>
<b>Gen Set Options</b> (available as factory options)	<ul style="list-style-type: none"><li>+ Versions with different voltages</li><li>+ Spark arrester muffler</li><li>+ AMF/ATS panel for auto start operation</li></ul>
<b>Accessories on Request</b>	<ul style="list-style-type: none"><li>+ Not available</li></ul>
<b>Noise Level</b>	+ Lwa 96 (71 dB at 7m) Homologated in accordance with the "Directive 2000/14/EC"
<b>AC Generator 50 Hz</b>	<ul style="list-style-type: none"><li>+ Type Gen Set asynchronous self-excited and self-protected</li><li>+ Three-phase power (stand by) 15 kVA - 400 V</li><li>+ Three-phase power (prime) 13,5 kVA - 400 V</li><li>+ Single-phase power (max.) 10 kVA - 230 V</li><li>+ Power Factor 0,8</li></ul>
<b>Diesel Engine 3000 rpm</b>	<ul style="list-style-type: none"><li>+ Type <b>Lombardini 9LD625-2</b> - 2 cyl. - 28,5 HP (21 kWm) - 1248 cm<sup>3</sup></li><li>+ Fuel diesel</li><li>+ Cooling system air</li><li>+ Starting system electric</li><li>+ Fuel tank capacity 38 l</li><li>+ Fuel consumption @ 75% 4,7 l/h</li></ul>
<b>Other Features</b>	<ul style="list-style-type: none"><li>+ Insulation Class F</li><li>+ Mechanical Protection IP 23</li><li>+ Dimensions (L x W x H) 1400 x 630 x 1023 mm (trailer not included)</li><li>+ Dry Weight 380 kg</li></ul>

## MG 15/10 S-L

 **GenSet**

