

MG 23 SS-Y

SUPER SILENCED THREE-PHASE POWER GENERATOR / OUTPUT POWER **22,5 KVA** THREE-PHASE AND **7,5 KVA** SINGLE-PHASE / DIESEL ENGINE **1500 RPM**

Gen Set Features	<ul style="list-style-type: none"> + ATS connector / RC connector + DAS, auto engine protection shutdown system with warning lights in case of: <ul style="list-style-type: none"> - battery charger failure - high coolant temperature - low fuel level - low oil pressure + 12V built-in battery with electric start + Frequencymeter + Voltmeter with phase to phase selector switch + Fuel level gauge 	<ul style="list-style-type: none"> + 1 x 32A, 400 V - 50 Hz three-phase EEC socket protected by 4-pole circuit breaker + 1 x 32A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker + Earth Leakage Circuit Breaker (ELCB) + Emergency STOP button + Automatic Voltage Regulator (AVR) + Central lifting eye + Two-wheels site tow undercarriage (GRT2W) 	
Gen Set Options (available as factory options)	<ul style="list-style-type: none"> + Versions with different voltages + 60 Hz version + Engine water heaters powered by mains 230V - 50 Hz 	<ul style="list-style-type: none"> + Spark arrester muffler + Electronic frequency regulator 	
Accessories on Request	<ul style="list-style-type: none"> + Remote Start/Stop kit by cable (20m) + AMF/ATS panel for auto start operation + Bunded base to retain all liquids + Skid base for use directly on the ground 		
Noise Level	+ Lwa 93	(68 dB at 7m)	Homologated in accordance with the "Directive 2000/14/EC"
AC Generator 50 Hz	+ Type	synchronous	
	+ Three-phase power (stand by)	22,5 kVA - 400 V	
	+ Three-phase power (prime)	20,2 kVA - 400 V	
	+ Single-phase power (max.)	7,5 kVA - 230 V	
	+ Power Factor	0,8	
Diesel Engine 1500 rpm	<ul style="list-style-type: none"> + Type Yanmar 4TNV-88 - 4 cyl. - 24 HP (17,6 kWm) - 2190 cm³ + Fuel diesel + Cooling system water + Starting system electric + Fuel tank capacity 67 l + Fuel consumption @ 75% 4,4 l/h 		
Other Features	+ Insulation Class	H	
	+ Mechanical Protection	IP 23	
	+ Dimensions (L x W x H)	1500 x 700 x 1185 mm (trailer not included)	
	+ Dry Weight	644 kg	

MG 23 SS-Y

