

MG 5/4 I-HE

PORTABLE THREE-PHASE POWER GENERATOR / OUTPUT POWER
5,5 KVA THREE-PHASE AND **4 KVA** SINGLE-PHASE /
PETROL ENGINE **3000 RPM**

| | |
|--|--|
| Gen Set Features | <ul style="list-style-type: none">+ Low oil level cut out device+ 1 x 16A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker+ 2 x 16A, 230 V - 50 Hz single-phase EEC socket (2 kVA + 2 kVA) protected by circuit breaker+ Earth Leakage Circuit Breaker (ELCB) |
| Gen Set Options (available as factory options) | <ul style="list-style-type: none">+ Versions with different voltages+ 60 Hz version |
| Accessories on Request | <ul style="list-style-type: none">+ Trolley: two-wheels and handles |
| Noise Level | + LWA 95 (70 dB at 7m) |
| AC Generator 50 Hz | <ul style="list-style-type: none">+ Type synchronous+ Three-phase power (max.) 5,5 kVA - 400 V+ Single-phase power (max.) 2 kVA - 230 V+ Power Factor 0,8 |
| Petrol Engine 3000 rpm | <ul style="list-style-type: none">+ Type Honda GX 270 OHV - 1 cyl. - 9 HP (6,6 kWm) - 270 cm³+ Fuel petrol+ Cooling system air+ Starting system manual recoil+ Fuel tank capacity 6 l+ Fuel consumption @ 75% 2,2 l/h |
| Other Features | <ul style="list-style-type: none">+ Insulation Class H+ Mechanical Protection IP 23+ Dimensions (L x W x H) 720 x 480 x 515 mm+ Dry Weight 78 kg |

MG 5/4 I-HE

