

MG 6/5 I-D/AE-Y

PORTABLE THREE-PHASE POWER GENERATOR / OUTPUT POWER
6 KVA THREE-PHASE AND **5 KVA** SINGLE-PHASE /
DIESEL ENGINE **3000 RPM**

Gen Set Features	<ul style="list-style-type: none">+ Low oil pressure and battery charger warning lights+ 12V built-in battery with electric start+ 1 x 16A, 400 V - 50 Hz three-phase EEC socket+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ Earth Leakage Circuit Breaker (ELCB)+ Voltmeter+ Fuel level gauge
Gen Set Options (available as factory options)	<ul style="list-style-type: none">+ Versions with different voltages+ 60 Hz version+ AMF/ATS panel for auto start operation
Accessories on Request	<ul style="list-style-type: none">+ Trolley: two-wheels and handles
Noise Level	+ LWA 99 (74 dB at 7m)
AC Generator 50 Hz	<ul style="list-style-type: none">+ Type Gen Set asynchronous, self-excited and self-protected+ Three-phase power (max.) 6 kVA - 400 V+ Single-phase power (max.) 5 kVA - 230 V+ Power Factor 0,8
Diesel Engine 3000 rpm	<ul style="list-style-type: none">+ Type Yanmar L100 AE - 1 cyl. - 10 HP (7,4 kWm) - 406 cm³+ Fuel diesel+ Cooling system air+ Starting system electric (and manual)+ Fuel tank capacity 5,5 l+ Fuel consumption @ 75% 1,7 l/h
Other Features	<ul style="list-style-type: none">+ Insulation Class F+ Mechanical Protection IP 23+ Dimensions (L x W x H) 920 x 460 x 570 mm+ Dry Weight 135 kg

MG 6/5 I-D/AE-Y

