

## MG 6/5 SS-Y

SUPER SILENCED THREE-PHASE POWER GENERATOR / OUTPUT POWER **6 KVA** THREE-PHASE AND **4 KVA** SINGLE-PHASE / DIESEL ENGINE **3000 RPM**

<b>Gen Set Features</b>	<ul style="list-style-type: none"><li>+ DAS, auto engine protection shutdown system with warning lights in case of:<ul style="list-style-type: none"><li>- low oil pressure</li><li>- battery charger failure</li><li>- low fuel level</li></ul></li><li>+ 12V built-in battery with electric start</li><li>+ Automatic idle device when no load is connected</li><li>+ Voltmeter</li><li>+ Engine hourmeter</li><li>+ 1 x 16A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker</li><li>+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker</li><li>+ Earth Leakage Circuit Breaker (ELCB)</li><li>+ Delta / Star selector</li><li>+ Emergency STOP button</li><li>+ AMF connector / RC connector</li><li>+ Bunded base to retain all liquids</li><li>+ Central lifting eye</li></ul>
<b>Gen Set Options</b> (available as factory options)	<ul style="list-style-type: none"><li>+ Versions with different voltages</li><li>+ 60 Hz version</li></ul>
<b>Accessories on Request</b>	<ul style="list-style-type: none"><li>+ Trolley: two-wheels and handles</li><li>+ AMF/ATS panel for auto start operation</li><li>+ Remote Start/Stop kit by cable (20m)</li></ul>
<b>Noise Level</b>	+ Lwa 92 (67 dB at 7m) Homologated in accordance with the "Directive 2000/14/EC"
<b>AC Generator 50 Hz</b>	<ul style="list-style-type: none"><li>+ Type synchronous</li><li>+ Three-phase power (max.) 6 kVA - 400 V</li><li>+ Single-phase power (max.) 4 kVA - 230 V</li><li>+ Power Factor 0,8</li></ul>
<b>Diesel Engine 3000 rpm</b>	<ul style="list-style-type: none"><li>+ Type <b>Yanmar L100AE</b> - 1 cyl. - 10 HP (7,4 kWm) - 406 cm<sup>3</sup></li><li>+ Fuel diesel</li><li>+ Cooling system air</li><li>+ Starting system electric</li><li>+ Fuel tank capacity 21 l</li><li>+ Fuel consumption @ 75% 1,7 l/h</li></ul>
<b>Other Features</b>	<ul style="list-style-type: none"><li>+ Insulation Class H</li><li>+ Mechanical Protection IP 23</li><li>+ Dimensions (L x W x H) 1100 x 600 x 830 mm</li><li>+ Dry Weight 214 kg</li></ul>

## MG 6/5 SS-Y

