

MG 6/5 Y

PORTABLE THREE-PHASE POWER GENERATOR / OUTPUT POWER
6 KVA THREE-PHASE AND **3,5 KW** SINGLE-PHASE /
DIESEL ENGINE **3000 RPM**

Gen Set Features	+ 1 x 16A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker + 1 x 230 V - 50 Hz single-phase Schuko outlet protected by circuit breaker + Central lifting eye	
Gen Set Options (available as factory options)	+ Not available	
Accessories on Request	+ Not available	
Noise Level	+ L _{WA} 105	(80 dB at 7m)
AC Generator 50 Hz	+ Type synchronous + Three-phase power (max.) 6,5 kVA - 400 V + Power Factor 0,8 + Single-phase power (max.) 3,5 kW - 230 V + Power Factor 1	
Diesel Engine 3000 rpm	+ Type Yanmar L100AE - 1 cyl. - 10 HP (7,4 kWm) - 406 cm ³ + Fuel diesel + Cooling system air + Starting system manual recoil + Fuel tank capacity 5,5 l + Fuel consumption @ 75% 1,7 l/h	
Other Features	+ Insulation Class H + Mechanical Protection IP 23 + Dimensions (L x W x H) 820 x 580 x 610 mm + Dry Weight 105 kg	

MG 6/5 Y

